



CONCEALED HINGES B - 120° OPENING

60-1-4033

Zinc plated steel version: small flat side in raw steel.

Natural POM pin diameter 6.

For pin with groove, optimal use of circlips DIN 6799 RS4 or O-ring 99-7-3723 (on request).

Produced mainly in stainless steel, for a complete description of the materials contact us.

A (length)	60 mm
Material	steel

C 2.5 mm D (pin diameter) 6 Finish zinc plated zinc plated grooved pin 2.5 mm by 5.3 12×6.5 2.5 mm c 2.5 mm	Weight (g)	102 g
Finish Zinc plated Zinc plated grooved pin 258 24 24 24 24 24 24 24 26 27 28 29 20 20 20 20 20 20 20 20 20	С	2.5 mm
Pin material 2 inc plated grooved pin 2 sc.5 2 sc.5 2 sc.8 2 sc.8	D (pin diameter)	6
12 x 6.5 88 74 52 88 52 81 24 24 24 24 24 24 24 24 24 24 24 24 24 2	Finish	zinc plated
6 20.4 DIN 6799 RS4	4 84 54 57 57 57 57 57 57 57 57 57 57 57 57 57	S

60-1-4034 & 62-1-3758

60-1-4032 & 62-1-3756

60-1-4033 & 62-1-3757